






FLASH SECURITY LIGHTS PANELS

COMPARATIVE TABLE



PANELS NAME	ITS FLASH 6	ITS FLASH 6+	ITS FLASH 9+
REFERENCE	ITSF6	ITSF6+	ITSF9HOMG2
LED TYPE	RVB SMD2727	RVB SMD2727	RVB
PIXEL PITCH	6 mm	6 mm	16 mm
RESOLUTION	96 x 96 pixels	96 x 96 pixels	96 x 96 pixels
PIXEL DENSITY	27 777 pixels/m ²	27 889 pixels/m ²	2 500 pixels/m ²
BEST VIEWING ANGLE	Horizontal 160° Vertical 120°	Horizontal 160° Vertical 120°	Horizontal 40° Vertical 15°
BRIGHTNESS	8500 cd/m ²	8500 cd/m ²	42000 cd/m ²
VISIBILITY	300 m • 984 ft	300 m • 984 ft	500 m • 1640,4 ft
COMMUNICATION	Radio 2,4 GHz RS-485 (2 wires)	Radio 2,4 GHz RS-485 (2 wires)	Radio 2,4 GHz RS-485 (2 wires)
DIMENSIONS	576 x 576 x 95 mm 22,4 x 22,4 x 3,7 in	576 x 576 x 175 mm 22,4 x 22,4 x 6,9 in	854 x 854 x 176 mm 33,6 x 33,6 x 6,9 in
WEIGHT	9,2 kg • 19,8 lb	10 kg • 22 lb	25 kg • 55,1 lbs
MATERIAL	Aluminum	Aluminum	Aluminum
POWER SUPPLY	220 VAC / 50 Hz	220 VAC / 50 Hz	220 VAC / 50 Hz
AVERAGE POWER	400 W/m ²	450 W/m ²	1000 W/m ²
LED LIFE SPAN	100 000 Hours	100 000 Hours	40 000 Hours
PROTECTION LEVEL	IP55	IP55	IP55
WORKING TEMPERATURE	-25°C → +55°C • -13°F → 131°F	-20°C → +65°C • -4°F → 149°F	-20°C → +65°C • -4°F → 149°F
ACCESS FOR MAINTENANCE	On the back	On the front	On the front
MODULAR PANELS	Yes	No	No
BACK DISPLAY ON THE PANEL'S BACK	No	Yes • 32 x 32 pixels	Yes • 48 x 48 pixels
WARRANTY	2 years	2 years	2 years

ACCESSORIES



ITS FLASH MANAGER SOFTWARE

Easily manage your lights.

REF. ITSFM



ITS CONTROL BOX

Easily control ITS Flash Manager software and manage your lights.

3 MODELS AVAILABLE

6 keys

REF. ITSCB6-F

15 keys

REF. ITSCB15-F

32 keys

REF. ITSCB32-F



ITS FLASH REMOTE CONTROL

Control your lights remotely.
Two models available :

Control a single panel :


REF. ITSFRC

Control all panels :

REF. ITSFGRC

10 customizable buttons

REF. ITSFRC10



PROTECTIVE VISOR

Protect the ITS Flash 6 panel from bad weather.

REF. ITSF6-V

PROTECTIVE VISOR

Protect the ITS Flash 6+ panel from bad weather.

REF. ITSF6P-V

