



# TRANSPONDERS

## COMPARATIVE TABLE

MADE IN FRANCE



LOOP TYPE	PASSIVE LOOP						ACTIVE LOOP		ACTIVE RF LOOP
TRANSPONDER	COBRA 200 WIRED	COBRA 360 WIRED	COBRA 360 MULTI-PILOT	LS WIRED AND RECHARGEABLE	ELITE WIRED AND RECHARGEABLE	ELITE MULTI-PILOT	RC	RT Waterproof	RF Radio 868 / 915 Mhz
REFERENCE	ITSCOBRA200F	ITSCOBRA360F	ITSCOBRA360M	ITSTLS ITSTLSB3	ITSTEF ITSTEB3	ITSTMPF	ITSTRC	ITSTRT	ITSTRF
POWER SUPPLY	12 V (2 wires)	Ni-MH battery	12 V (2 wires)	12 V (2 wires) Ni-MH battery	12 V (2 wires) Ni-MH battery	12 V (2 wires)	3V Button Battery CR2450 Lithium	3V Button Battery CR2450 Lithium	3V Button Battery CR2450 Lithium
AUTONOMY	Permanent supply	Permanent supply	Permanent supply	Permanent supply 4 days	Permanent supply 4 days	Permanent supply	3/4 years or 122 000 passings	3/4 years or 122 000 passings	3/4 years or 122 000 passings
CHARGE CYCLES	-	-	-	14 - 18h	14 - 18h	-	Interchangeable Battery	Non-replaceable Battery	Interchangeable Battery
MAXIMUM DETECTION HEIGHT	2,80 m • 9,2 ft	2,80 m • 9,2 ft	2,80 m • 9,2 ft	2,80 m • 9,2 ft	2,80 m • 9,2 ft	2,80 m • 9,2 ft	1,20 m • 3,9 ft	1,20 m • 3,9 ft	4 m • 13,1 ft
MAXIMUM DETECTION SPEED	200 km/h 124,3 mph	360 km/h 223,7 mph	360 km/h 223,7 mph	200 km/h 124,3 mph	360 km/h 223,7 mph	360 km/h 223,7 mph	120 km/h 74,6 mph	120 km/h 74,6 mph	140 km/h 87 mph
DIMENSIONS	81 x 52 x 22 mm 3,2 x 2 x 0,9 in	81 x 52 x 22 mm 3,2 x 2 x 0,9 in	81 x 52 x 22 mm 3,2 x 2 x 0,9 in	65 x 44 x 22 mm 2,6 x 1,7 x 0,9 in 80 x 50 x 23 mm 3,1 x 1,9 x 0,9 in	65 x 44 x 22 mm 2,6 x 1,7 x 0,9 in 80 x 50 x 23 mm 3,1 x 1,9 x 0,9 in	65 x 44 x 22 mm 2,6 x 1,7 x 0,9 in	48 x 28 x 12 mm 1,9 x 1,1 x 0,5 in	48 x 28 x 12 mm 1,9 x 1,1 x 0,5 in	48 x 28 x 12 mm 1,9 x 1,1 x 0,4 in
WEIGHT	90 g	90 g	90 g	80 g	80 g	80 g	19 g • 0,7 oz	19 g • 0,7 oz	23 g • 0,8 oz
TEMPERATURE RANGE	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	-20°C to +70°C -4°F to 158°F	-20°C to +70°C -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F
FIXING	Mounting holes in the transponder frame	Mounting holes in the transponder frame	Mounting holes in the transponder frame	Mounting holes in the transponder frame Holder and clip	Mounting holes in the transponder frame Holder and clip	Mounting holes in the transponder frame	PVC Holder or Neopren Strap	PVC Holder or Neopren Strap	PVC Holder or Neopren Strap
SPORT	Motocross Supercross Kartcross Rallycross Follcar Truck Karting	Car Speed Bike Truck Karting	Car endurance Truck endurance Karting endurance	Motocross Supercross Kartcross Rallycross Follcar Truck Karting	Car Speed Bike Truck Karting	Car endurance Truck endurance Karting endurance	Rental Karting Cycling Running Cross skiing Roller Skating	Rental Karting Cycling Running Cross skiing Roller Skating Triathlon	Rental Karting Cycling Running Cross skiing Roller Skating Motocross
WARRANTY	2 years	2 years	2 years	2 years	2 years	2 years	2 years (battery not guaranteed)	2 years (battery not guaranteed)	2 years (battery not guaranteed)

