

TRANSPONDERS



















					6.0		•		- 1
MADE IN FRANCE	PASSIVE LOOP USE				ACTIVE LOOP USE				
TRANSPONDERS	WIRED ELITE	RECHARGEABLE ELITE	WIRED LS	RECHARGEABLE LS	RC	RT Waterproof	RF Radio 868 / 915 Mhz	RF-S Radio 868 / 915 Mhz Waterproof	RF-I Radio 868 / 915 Mhz Waterproof
REFERENCE	ITSTEF	ITSTEB3	ITSTLSF	ITSTLSB3	ITSTRC	ITSTRT	ITSTRF	ITSTRF-S	ITSTRF-I
WARRANTY	2 years	2 years	2 years	2 years	2 years (battery not guaranteed)	2 years (battery not guaranteed)	2 years (battery not guaranteed)	2 years	2 years
POWER SUPPLY	12V (2 wires)	Ni-MH Battery	12V (2 wires)	Ni-MH Battery	Button Battery 3V CR2450 Lithium	Button Battery 3V CR2450 Lithium	Button Battery 3V CR2450 Lithium	Button Battery 3V CR2032 Lithium	Button Battery 3V CR2032 Lithium
AUTONOMY	Permanent supply	4 days	Permanent supply	4 days	3/4 years or 122 000 transit	3/4 years or 122 000 transit	3/4 years or 122 000 transit	3 years	3/4 years or 122 000 transit
CHARGE CYCLE	-	14 - 18h	-	14 - 18h	Interchangeable Battery	Non-replaceable Battery	Interchangeable Battery	Non-replaceable Battery	Non-replaceable Battery
MAX DETECTION HEIGHT	2,80 m / 9,2 ft	2,80 m / 9,2 ft	2,80 m / 9,2 ft	2,80 m / 9,2 ft	1,20 m / 3,93 ft	1,20 m / 3,93 ft	4 m / 13,1 ft	4 m / 13,1 ft	4 m / 13,1 ft
MAX SPEED DETECTION	360 km/h / 223,7 mph	360 km/h / 223,7 mph	200 km/h / 124,3 mph	200 km/h / 124,3 mph	120 km/h / 74,6 mph	120 km/h / 74,6 mph	140 km/h / 87 mph	140 km/h / 87 mph	140 km/h / 87 mph
DIMENSIONS	80 x 50 x 23 mm 3,1 x 1,9 x 0,9 in	65 x 44 x 22 mm 2,6 x 1,7 x 0,9 in	80 x 50 x 23 mm 3,1 x 1,9 x 0,9 in	65 x 44 x 22 mm 2,6 x 1,7 x 0,9 in	48 x 28 x 12 mm 1,9 x 1,1 x 0,5 in	48 x 28 x 12 mm 1,9 x 1,1 x 0,5 in	48 x 28 x 12 mm 1,9 x 1,1 x 0,5 in	42 x 43 x 6 mm 1,6 x 1,7 x 0,2 in	34 x 50 x 9 mm 1,3 x 2 x 0,35 in
WEIGHT	80 g / 2,8 oz	80 g / 2,8 oz	80 g / 2,8 oz	80 g / 2,8 oz	19 g / 0,7 oz	19 g / 0,7 oz	23 g / 0,8 oz	12 g / 0,4 oz	16 g / 0,56 oz
TEMPERATURE RANGE	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F	from -20°C to 70°C from -4°F to 158°F
SET	No need holder	Holder and Clip	No need holder	Holder and Clip	PVC Holder or Neopren Strap	PVC Holder or Neopren Strap	PVC Holder or Neopren Strap	Neopren Strap	Neopren Strap
SPORT	Cars Speed Bike Truck Karting	Cars Speed Bike Truck Karting	Motocross Supercross Kartcross Rallycross Follcar - Karting	Motocross Supercross Kartcross Rallycross Follcar - Karting	Rental Karting Cycling Running Cross skiing Roller Skating	Rental Karting Cycling - Running Cross skiing Roller Skating Triathlon	Rental Karting Cycling - Running Cross skiing Roller Skating Motocross	Cycling Running Cross skiing Roller Skating Triathlon	Cycling Running Athletics - Triathlon Roller skating Karting



Elite and LS rechargeable transponders are also sold with charging suitcase of maximum 40 transponders (the charger and the power supply are integrated to the suitcase).

Ref: ITSACH503

INDIVIDUALS KITS / ELITE AND LS

Elite and LS rechargeable transponders are also sold in individual kit uncluding 1 holder, 1 clip and 1 charger.

(LS model)

TAG HEUER BY CHRONELEC: EXPERIENCE AND TECHNOLOGY

The experience of **TAG Heuer by Chronelec** in timing, allowed the elaboration of a whole range of transponders.

Their reliable technology makes these transponders, **undeniable and essential precision tools**. Whatever the sport, the level of competition, the technical constraints, you will always find the right transponders for your needs.

